

Terms of acceptance mixed construction and demolition waste



Waste from construction and demolition work. Construction and demolition waste is a mixed waste flow that has to be separated

Permitted:

Mixed composition:

All dry non-hazardous waste substances required to be kept separate at the source.

- Construction and demolition waste without **overheating**
- Rubble
- Broken up road building materials
- Plastics (PVC, HDPE, hard plastics, film, bigbags, etc.)
- Metals
- Residual construction materials
- Paper and cardboard
- Film
- Plaster
- Cellular concrete (e.g. Ytong)
- Wood
- Clean roof gravel
- Car tyres
- Agricultural film
- Mattresses and sofas
- E-waste

Minimum quantities permitted:

- Adherent clean soil
- Insulation material (< 10%)
- Glass (<2%)
- Prunings
- Floor covering (<5%)

Not permitted:

- × Hazardous waste substances
- × Paint and filler syringes
- × Ruberoid/roofing
- × Suspected asbestos materials
- × Tar-bearing asphalt
- × Chimney waste and soot residue (incl. slag and ash)
- × GFT
- × PMD
- × White and brown goods such as fridges that contain hazardous substances
- × Railway ballast

- x Screened sand
- x Rubble from soil materials, fire, sanitation, mandatory drainage or landfill mining